



Gypsum Plaster (POP)

Description

Aneeb Bond+ Gypsum Plaster is natural gypsum [$\text{CaSO}_4 + 1/2\text{H}_2\text{O}$], which is mined in rock form. It essentially consists of retarded hemihydrate Gypsum Plaster characterized by lower density & high thermal insulation properties.

During Calcination at a high temperature which converts raw Gypsum to fine powder form. It is further subjected to thorough sieving process to enhance quality and to bring out superior plastering grade. In plastering stage, about 16 - 17 litres of water is mixed with 25kg material and thus the water content removed at manufacturing stage is regained and gypsum is transformed back into its strong crystal form. The product has an initial setting time of 10 - 15 minutes. Further processes like painting, fixtures can be started after 72 hours once plaster is fully dried.

Aneeb Plaster is the only gypsum plaster which is very natural in its form and gives a ultra white and bright finish. It's smoothness gives great coverage, workability and high productivity to the plasterer. Hence great wall finish with reduced time and cost to the customer. This is how we add value to our customer's business.

Benefits of *Aneeb Gypsum Plaster POP*



- Natural White Colour
 - Humidity resistant
 - Crack free
 - No powdering
 - Fungus Free
 - Fire resistant
-
- Lightweight
 - Excellent strength on drying
 - Thermal resistance
 - High coverage
 - Purity –free from Silica
 - Affordable

Application:

- Doesn't need any kind of primer on it before application of paint/distemper thus saving time & cost. Can be applied on interior walls & ceilings.
- Gives a smooth, white finish surface, which effectively reduces the consumption of subsequent Paints & gives true tone of color.
- It is in dry powder form and does not produce any kind of unpleasant smell at the time of application.
- It is Eco-Friendly. It does not contain lead, oil or toxic material. Has anti-carbonation properties thus protects the reinforcement bars from corrosion.
- Does not require any water curing after application thus saving time & cost.
- Accepts any kind of paint or distemper application on it.
- Can be applied on used surface after proper preparation. It prevents the growth of algae and fungi on walls.

Specification

- Can be directly applied, single coat application.
- Free from shrinkage and crack and powdering
- High coverage up to 90 m²/t
- Ultra white and smooth finish
- Enhanced light reflection, imparts true colour tone and gloss for paint.
- Compatible with any type of paint.
- Highly moisture resistant Hygienic -Does not allow bacteria or fungus getting formed on it.

Shelf Life & Storage:

6 months from the date of manufacturing.

Packing

25 Kg Bag